


EB-L1050U (white)



DATASHEET / BROCHURE



The fit-and-forget laser projector with interchangeable lenses, that's ideal for scenarios that demand large, detailed and powerful images.

This affordable 5,500 lumens installation projector, with interchangeable lenses and laser image quality, is sold as 'body only' which allows the user to choose the most appropriate lens from Epson's wide range. With flexible installation, low maintenance, and a modern and compact design, this laser projector can be used in a range of large venues.

Superior image quality

The EB-L1050U projects clear whites, vivid details, deep blacks, defined shadows and high contrast imagery.

Flexible installation

The compact, unobtrusive design allows this projector to blend seamlessly into most environments. Its 360 degree usage arc and tilt-free technology, mean you can project in any direction.

Interchangeable lenses

Just as a specific scenario dictates which camera lens is most appropriate to use – the same is true with different projection environments. That's why we've designed our projector body to accommodate different lenses. There are 11 interchangeable Epson lenses available, covering short to long-throw projection.

Reliable

Epson has developed a 'maintenance-free light source' alternative laser projector range that's truly fit-and-forget.

KEY FEATURES

- **Fit and forget**
Fit almost anywhere. 360 degree angle projection freedom
- **Lens support**
Supports a wide selection of Epson interchangeable lenses
- **Enhanced design**
Clean, simple, compact and discreet design. White version.
- **Image quality**
5,500 lumens, 4K enhancement, CLO, 3LCD, 2000:1 native contrast
- **Support**
Five year / 20,000 hour warranty



EPSON
WORLD LEADER
IN PROJECTORS
Source: Futuresource Consulting Ltd.

EPSON[®]
EXCEED YOUR VISION

PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System	3LCD Technology
LCD Panel	0.76 inch with C2 Fine

IMAGE

Colour Light Output	5,500 lumen- 3,850 lumen (economy) in accordance with IDMS15.4
White Light Output	5,500 lumen - 3,850 lumen (economy) in accordance with ISO 21118:2012
Portrait Colour Light Output	5,500 lm
Portrait White Light Output	5,500 lm
Resolution	WUXGA, 1920 x 1200, 16:10
High Definition	4K enhancement
Aspect Ratio	16:10
Contrast Ratio	Over 2,500,000 : 1
Native Contrast	2,000 : 1
Light source	Laser
Laser Light source	20,000 Hours Durability High, 30,000 Hours Durability Eco
Keystone Correction	Manual vertical: $\pm 45^\circ$, Manual horizontal $\pm 30^\circ$
Colour Reproduction	upto 1.07 billion colours

OPTICAL

Projection Ratio	1.44 - 2.33:1
Zoom	Motorized, Factor: 1 - 1.6
Lens Shift	Motorized - Vertical $\pm 67\%$, horizontal $\pm 30\%$
Image Size	50 inches - 1,000 inches
Projection Lens F Number	1.7 - 2.3
Focal Distance	24 mm - 38.2 mm
Focus	Motorized
Interchangeable Lens	Yes
Projection Distance Wide	1.5 m - 31.6 m (50 inch screen)

CONNECTIVITY

Interfaces	USB 2.0 Type B (Service Only), RS-232C, WLAN (2x), VGA in, DVI in, HDMI in, BNC in, HDBaseT, Stereo mini jack audio out, Stereo mini jack audio in (3x), Ethernet interface (100 Base-TX / 10 Base-T), VGA out, HDMI (HDCP 2.2), Wireless LAN IEEE 802.11b/g/n (WiFi 4) (optional)
------------	--

GENERAL

Energy Use	345 W, 252 W (economy), 0.5 W (standby)
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz
Product dimensions	545 x 164 x 436 mm (Width x Depth x Height)
Product weight	16.9 kg
Noise Level	Normal: 34 dB (A) - Economy: 30 dB (A) (4K enhancement OFF)
Colour	White

EB-L1050U (white)

WHAT'S IN THE BOX

- Cable cover
- Power cable
- Remote control incl. batteries
- Lens cap
- Quick Start Guide
- CD Manual

OPTIONAL ACCESSORIES

EB-L1050U (white)

- Ceiling Mount (White) - ELPMB22
V12H003B22
- Air Filter - ELPAF46
V13H134A46
- Ceiling Mount - ELPMB48 High EB-G7000/L1000
V12H803010
- 3D Polarizer - ELPPL01
V12H618A01
- Wireless LAN Adapter - ELPAP10
V12H731P01
- Active Speakers (2 x 15W) - ELPSP02
V12H467040DA
- Ceiling Mount - ELPMB47 Low EB-G7000/L1000
V12H802010
- Ceiling Pipe (450mm) - ELPPF13
V12H003P13
- Ceiling Pipe (700mm) - ELPPF14
V12H003P14

OPTIONAL LENSES

- Lens - ELPLM11 - Mid throw 4 - G7000/L1000 series
V12H004MOB
- Lens - ELPLM08 - Mid throw 1 - G7000/L1000 series
V12H004M08
- Lens - ELPLX01W - UST lens G7000 series & L1100,1200,1300,1400/5U
V12H004Y01
- Lens - ELPLX01 - UST lens G7000 series & L1100,1200,1300,1400/5U
V12H004X01
- Lens - ELPLM10 - Mid throw 3 - G7000/L1000 series
V12H004M0A
- Lens - ELPLW08 - Wide throw
V12H004W08
- Lens - ELPLW06 - L1500U/1505U wide zoom 2
V12H004W06
- Lens - ELPLU04 - G7000 & L1000 Series ST off axis 2
V12H004U04
- Lens - ELPLW05 - G7000 & L1000 Series wide zoom 1
V12H004W05
- Lens - ELPLL08 - Long throw - G7000/L1000 series
V12H004L08
- Lens - ELPLU03 - G7000 & L1000 Series ST off axis 1
V12H004U03

LOGISTICS INFORMATION

SKU	V11H942940
EAN code	8715946672618
Country of Origin	China



For more information please contact:

Home users: 0343 90 37766
Business users*: 0871 42 37766
Republic of Ireland: 01 436 7742
Or visit us at <https://www.epson.co.uk/contactus>
* 10p per minute plus network extras.

Web: www.epson.co.uk
www.epson.ie

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.
Last extracted: 2019-09-06

EPSON[®]