

# Lens Specification – PU1006 > PU1008

Model No	Throw Ratio WUXGA	Lens Shift WUXGA Vertical / Horizontal	Weight (KG)	Dimension	Projector Compatibility
ELPLX01S	0.35:1	+17% / ±10%	3.5	215mm*321mm*164mm	All lenses are compatible with the following projectors: L1000, L1100, L1105, L1300, L1405, L1050U, L1070U, L1075U, PU1008W/B, PU1007W/B, PU1008W/B
ELPLU03S	0.65 - 0.78:1	±67% / ±30%	2.3	150mm*240mm	
ELPLU04	0.87 - 1.05:1	±67% / ±30%	3.1	150mm*267mm	
ELPLW05	1.04 - 1.46:1	±67% / ±30%	1.45	135mm*200.5mm	
ELPLM08	1.44 - 2.32:1	±67% / ±30%	1.2	115mm*191mm	
ELPLM15	2.16 - 3.48:1	±67% / ±30%	1.9	111.2mm*202mm	
ELPLM10	3.32 - 5.06:1	±67% / ±30%	2.2	104mm*243mm	
ELPLM11	4.85 - 7.38:1	±67% / ±30%	2.2	104mm*245mm	
ELPLL08	7.21 - 10.11:1	±67% / ±30%	2.2	104mm*247mm	

# Lens Specification – PU2010, L15xx, L17xx, L20000

Model No	Throw Ratio WUXGA	Throw Ratio SXGA+	Lens Shift WUXGA Vertical / Horizontal	Lens Shift SXGA+ Vertical / Horizontal	Weight (KG)	Dimension	Projector Compatibility
ELPLX02S	0.35:1	0.36:1	+25% / ±15%	±10% / ±5%	5	380mm*340mm*210mm	All lenses are compatible with: PU2010, L149x/L15xx/L17xx Series, L20000
ELPLU03S	0.48 - 0.57:1	0.49 - 0.59:1	±24% / ±10%	±16% / ±9%	2.3	150mm*240mm	
ELPLU04	0.64 - 0.77:1	0.66 - 0.8:1	±60% / ±18%	±55% / ±19%	3.1	150mm*267mm	
ELPLW05*	0.77 - 1.07:1	0.79 - 1.11:1	±24% / ±10%	±16% / ±9%	1.45	135mm*200.5mm	
ELPLW06	1.19 - 1.62:1	1.23 - 1.67:1	±60% / ±18%	±55% / ±19%	2.95	129.8mm*236mm	
ELPLW08	0.86 - 1.2:1	0.89 - 1.25:1	±60% / ±18%	±55% / ±19%	3.05	140mm*263.5mm	
ELPLM15	1.57 - 2.56:1	1.62 - 2.65:1	±60% / ±18%	±55% / ±19%	1.9	111.2mm*202mm	
ELPLM10	2.42 - 3.71:1	2.5 - 3.84:1	±60% / ±18%	±55% / ±19%	2.2	104mm*243mm	
ELPLM11	3.54 - 5.41:1	3.64 - 5.58:1	±60% / ±18%	±55% / ±19%	2.2	104mm*245mm	
ELPLL08	5.27 - 7.41:1	5.43 - 7.65:1	±60% / ±18%	±55% / ±19%	2.2	104mm*247mm	

\*projectors will run with reduced light output  
Document should be used for reference only and is not intended for exact measurements  
For use in EMEAR region only  
Rev 3.0 – Feb 2021